

# HUNTSMAN

BUILDING SOLUTIONS

**Featuring superior cohesion,  
Classic Ultra™ lets your  
sprayers experience:**

- Improved spraying techniques
- Up to 90% better cohesion than Classic Max
- Improved time management on the job site
- Eliminate pre-spray paddle mixing by hand. Exclusive Draw Mixer does all the work.
- Start spraying with drum temperatures as low as 60°F



## CLASSIC ULTRA™

OPEN-CELL SPRAY FOAM





**CLASSIC ULTRA™**  
OPEN-CELL SPRAY FOAM



**PRODUCT FEATURES**

- Core Density: 0.5 lb/ft<sup>3</sup>
- R-Value: R-3.7 per 1”
- No pre-spray hand paddle mixing. Draw Mixer does all the work!
- Up to 90% improved cohesion than Classic Max. Able to better stick to itself and substrates
- Allows sprayers to start spraying with drum temperatures as low as 60°F
- Can be sprayed in a wide temperature range for applications, making it suitable for any climate
- No ignition barrier required for limited-access attic and crawlspace applications
- Low VOC allowing for re-entry in 1 hour and re-occupancy in 2 hours (at 10ACH)
- GREENGUARD Gold certification

THICKNESS (inches)	R-VALUE (°F•ft <sup>2</sup> •h/Btu)
1	R-3.7
3.5	R-13
4	R-14
5.5	R-20

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your energy savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your energy use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on energy. To get the marked R-value, it is essential that this insulation be installed properly.

