HUNTSMAN BUILDING SOLUTIONS

RCS[™] 6000 SAFETY DATA SHEET

SECTION 1: Identification of the	substance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixture
rade name	: RCS 6000 Acrylic Clear Sealant
roduct code	: RCS 6000 Roof Shingle Sealer
1.2. Relevant identified uses of the	substance or mixture and uses advised against
lse of the substance/mixture	: Use to seal, protect and preserve roof shingles to extend the life of the roof.
1.3. Details of the supplier of the sa	fety data sheet
Huntsman Building Solutions 3315 E. Division Street, Arlington, TX 76011 Tel: 817-640-4900 , 888-224-153 sdsinfo@huntsmanbuilds.com	
1.4. Emergency telephone number	
mergency number	: CARECHEM (866) 928-0789
SECTION 2: Hazards identification	on
2.1. Classification of the substance	
GHS-US classification	
Skin Sens. 1	H317
Carc. 1B	H350
Full text of H-statements: see section 16	
ignal word (GHS-US)	GHS07 GHS08 : Danger
lazard statements (GHS-US)	 H317 - May cause an allergic skin reaction H350 - May cause cancer
Precautionary statements (GHS-US)	 P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P261 - Avoid breathing mist, spray, vapours P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear eye protection, protective gloves P302+P352 - If on skin: Wash with plenty of water P308+P313 - If exposed or concerned: Get medical advice/attention P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P405 - Store locked up P501 - Dispose of contents/container to comply with applicable local, national and international regulation.
2.3. Other hazards	
ther hazards which do not result in classifica 2.4. Unknown acute toxicity (GHS-U Not applicable	
SECTION 3: Composition/inform	ation on ingradiants
•	
3.1. Substance	
Not applicable	

BUILDING SOLUTIONS

3.2. Mixture				
Name		Product identifier	%	GHS-US classification
Distillates, petroleum, solvent-dewaxed heavy para	affinic	(CAS No) 64742-65-0	0,1 - 0,5	Carc. 1B, H350
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl-		(CAS No) 64359-81-5	0,02 - 0,21	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Full text of H-statements: see section 16				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general		ever give anything by mouth to an u dvice (show the label where possible		
First-aid measures after inhalation	: A	llow breathing of fresh air. Allow the	victim to rest.	
First-aid measures after skin contact	by	emove affected clothing and wash a / warm water rinse. Wash with plent edical advice/attention. Wash conta	, of soap and water. I	f skin irritation or rash occurs: Get
First-aid measures after eye contact		inse immediately with plenty of wate ersist.	r. Obtain medical atte	ntion if pain, blinking or redness
First-aid measures after ingestion	: R	inse mouth. Do NOT induce vomitin	g. Obtain emergency	medical attention.
4.2. Most important symptoms and ef	fects, bo	th acute and delayed		
Symptoms/injuries after inhalation	: In	halation may cause irritation, cough	, short breathing.	
Symptoms/injuries after skin contact	ha	ay cause moderate irritation. This p as been reported to cause skin sens ause an allergic skin reaction.		
Symptoms/injuries after eye contact	: M	ay cause moderate irritation, includi	ng burning sensation,	tearing, redness or swelling.
Symptoms/injuries after ingestion	: A	bdominal pain, nausea.		
SECTION 5: Firefighting measures 5.1. Extinguishing media	;			
Suitable extinguishing media	: F	oam. Dry powder. Carbon dioxide. V	Vater spray. Sand.	
Unsuitable extinguishing media	: D	o not use a heavy water stream.		
5.2. Special hazards arising from the	substanc	e or mixture		
Fire hazard		aterial can splatter above 100° C (2 arbon dioxide. Carbon monoxide.	12° F). Dried product	can burn. On combustion forms:
Explosion hazard	: N	o direct explosion hazard.		
Reactivity	: N	o dangerous reactions known under	normal conditions of	use.
5.3. Advice for firefighters				
Firefighting instructions		se water spray or fog for cooling exp nemical fire. Prevent fire-fighting wat		
Protective equipment for firefighters	: D	o not enter fire area without proper p	protective equipment,	including respiratory protection.
SECTION 6: Accidental release me	asures			
6.1. Personal precautions, protective				
6.1.1. For non-emergency personnel				
Protective equipment	: W	ear protective clothing as described	in Section 8 of this sa	afety data sheet.
Emergency procedures		vacuate unnecessary personnel.		
6.1.2. For emergency responders				
Protective equipment		quip cleanup crew with proper prote		mation refer to section 8 :
Emergency procedures		xposure-controls/personal protectior entilate area.	1.	
6.2. Environmental precautions				

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

BUILDING SOLUTIONS



6.3. Methods and material for cor	ntainment and cleaning up
For containment	 Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
6.4. Reference to other sections	
For further information refer to section 8	: Exposure-controls/personal protection. For disposal of residues refer to section 13 : Disposal considerations
SECTION 7: Handling and stor	age
7.1. Precautions for safe handling	
Precautions for safe handling	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing vapours, spray, mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage,	including any incompatibilities
Storage conditions	: Protect from freezing. Store in a dry, cool and well-ventilated place. Keep container closed when not in use.
7.3. Specific end use(s)	
No additional information available	
SECTION 8: Exposure controls	s/personal protection
8.1. Control parameters	
No additional information available	
8.2. Exposure controls	
Appropriate engineering controls	: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min at the point of vapour evolution.
Personal protective equipment	Avoid all unnecessary exposure. Protective goggles. Gloves.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	Chemical goggles or safety glasses. Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.
Respiratory protection	 Wear appropriate mask. If the occupational exposure limit is exceeded. Wear a NIOSH approved amine and ammonia respiratory cartridge or NIOSH approved air supplied breathing equipment.
Other information	Do not eat, drink or smoke during use.
SECTION 9: Physical and chen	nical properties
9.1. Information on basic physica	
Physical state	: Liquid

Colour	:	Clear to hazy
Odour	:	characteristic
Odour threshold	:	No data available
рН	:	8,5 - 9,5
Melting point	:	No data available
Freezing point	:	No data available

HUNTSMAN **BUILDING SOLUTIONS**

Boiling point	: 212 °F
Flash point	: 240 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Density Solubility	: 1,05 : Water: Soluble
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
VOC content	: 25 g/l

VOC content

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. **Chemical stability**

Stable at ambient temperature and under normal conditions of use. Hazardous polymerization will not occur.

10.3. Possibility of hazardous reactions

None known.

Conditions to avoid 10.4.

Avoid exposure to temperatures above 150 °F (65.6 °C).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On combustion, forms: Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological informati	on
11.1. Information on toxicological effects	
Likely routes of exposure	: Ingestion; Inhalation; Skin and eye contact
Acute toxicity	: Not classified
	(Based on available data, the classification criteria are not met)

RCS[™] 6000 SAFETY DATA SHEET

Skin corrosion/irritation	: Not classified
	(Based on available data, the classification criteria are not met)
	pH: 8,5 - 9,5
Serious eye damage/irritation	: Not classified
	(Based on available data, the classification criteria are not met)
	pH: 8,5 - 9,5
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure)	: Not classified
	(Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified
	(Based on available data, the classification criteria are not met)
Symptoms/injuries after inhalation	: Inhalation may cause irritation, cough, short breathing.
Symptoms/injuries after skin contact	: May cause moderate irritation. This product contains small amounts of an ingredient which
	has been reported to cause skin sensitization reactions in humans and guinea pigs. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: May cause moderate irritation, including burning sensation, tearing, redness or swelling.
Symptoms/injuries after ingestion	: Abdominal pain, nausea.
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Mixture not tested.
Distillates, petroleum, solvent-dewaxed hear	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
12.2. Persistence and degradability	
RCS 6000 Acrylic Clear Sealant	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
RCS 6000 Acrylic Clear Sealant	
Bioaccumulative potential	Not established.
· · · · · · · · · · · · · · · · · · ·	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	

Other	information

Effect on ozone layer

Effect on the global warming

: Avoid release to the environment.

: No additional information available

: No additional information available

SECTION 13: Disposal considera	tions
13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

BUILDING SOLUTIONS

SECTION 14: Transport information

RCS [™]	6000
SAFETY DATA	SHEET

Department of Transportation (DOT)		
In accordance with DOT		
Not regulated for transport		
Additional information		
Other information	:	No

: No supplementary information available.

ADR

No additional information available

Transport by sea No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information
15.1. US Federal regulations
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- (64359-81-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
15.2. International regulations
CANADA
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)
Listed on the Canadian DSL (Domestic Substances List)
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- (64359-81-5)
Listed on the Canadian NDSL (Non-Domestic Substances List)
EU-Regulations
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- (64359-81-5)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
National regulations
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl- (64359-81-5)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on NZIOC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

No additional information available

RCS[™] 6000 SAFETY DATA SHEET

SECTION 16: Other information

Full text of H-statements:

Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Sensitisation — Skin, category 1
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H350	May cause cancer

SDS US (GHS HazCom 2012)

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY HUNTSMAN BUILDING SOLUTIONS. HEREUNDER ARE GIVEN GRATIS AND HUNTSMAN BUILDING SOLUTIONS ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. HUNTSMAN BUILDING SOLUTIONS WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.