

HUNTSMAN

BUILDING SOLUTIONS



**SPRAY UP TO AN
R-49 IN A SINGLE
PASS**



*Developed with
>20% of Renewable
and Recycled Content*

HEATLOK[®] HFO HIGH LIFT

CLOSED-CELL SPRAY FOAM



HEATLOK[®] HFO HIGH LIFT

CLOSED-CELL SPRAY FOAM



PRODUCT FEATURES

- R-value = 7.4/inch*
- Spray 6.5" (R-49) in one pass
- Low VOC emission meets requirements for schools and healthcare facilities
- Superior yield, sprayability, adhesion and reduced gun clogging
- Formulated with Solstice[®] Liquid Blowing Agent's Ultra-low GWP of 1

REDUCE GLOBAL WARMING IMPACT WITH ULTRA-LOW GWP BLOWING AGENT

Heatlok[®] HFO High Lift, Huntsman Building Solutions' first product to leverage an ultra-low Global Warming Potential blowing agent, combines an R-value of 7.4 with a 6.5" lift to achieve an R-49 in a single pass. Spray to IRC Ceiling insulation code in less time than ever before.

Heatlok HFO High Lift leverages Honeywell's Solstice[®] Liquid Blowing Agent technology, which has a GWP of 1, 99.9% lower than traditional blowing agents. In compliance with the Montreal Protocol designed to lower the use of global warming potential gasses, Heatlok[®] HFO High Lift combines all of the benefits of Heatlok[®] with the industry's fourth generation blowing agent.

R-value	7.4 @ 1 inch
ASTM E-84	Flame Spread Index = 1
Application Temp Range	15 - 100°F (-9 - 38°C)
Yield	4500-5000 bd. ft. / set
Max Lift	6.5"

*Aged R-value at 4 inches per ASTM C518



Complies with the International Building Code[®] (IBC), the International Residential Code[®] (IRC), and the International Energy Conservation Code[®] (IECC).