

HUNTSMAN

BUILDING SOLUTIONS



IGNITION BARRIER FREE FOR UNVENTILATED ATTICS



*Developed with
>20% of Renewable
and Recycled Content*

SEALECTION[®] 500

OPEN-CELL SPRAY FOAM



SEALECTION® 500

OPEN-CELL SPRAY FOAM



PRODUCT FEATURES

- R-value = 7.4/inch*
- Spray 6.5" (R-49) in one pass
- Low VOC emission meets requirements for schools and healthcare facilities
- Superior yield, sprayability, adhesion and reduced gun clogging
- Formulated with Solstice® Liquid Blowing Agent's Ultra-low GWP of 1

R-value	3.81 @ 1 inch
Density	1/2 lb/ft ³

CUTS ENERGY COSTS BY 50%*

The same easily applied, open-cell spray foam that provides an efficient lifelong building envelope is now certified to the same test standards as our Classic Max and SWD's Quik-Shield 108

Sealection® 500 is an industry-leading formula of open-cell spray foam insulation that expands 120 times its liquid volume to insulate and seal all cracks, gaps and joints with a single application. It is easy to install and finish, and has now been tested and certified for use in unventilated attics without a prescribed ignition barrier. For more information, consult CCRR-1063 on the Huntsman Building Solutions website.

*Aged R-value at 4 inches per ASTM C518



Complies with the International Building Code® (IBC), the International Residential Code® (IRC), and the International Energy Conservation Code® (IECC).