

HUNTSMAN

BUILDING SOLUTIONS

SAFETY DATA SHEET H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name H2FOAM LITE PLUS
Product number H2FOAM LITE PLUS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Component of a Polyurethane System.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Huntsman Building Solutions (HBS)
Station Road, Roydon, King's Lynn, Norfolk, PE32 1AW, United Kingdom
Telephone: +44 (0)1485 500668
Email: info@demilecuk.com

E-mail address of person responsible for the SDS sds-records@ifs-group.com

1.4. Emergency telephone number

Emergency telephone +44 (0)7795 093 276, +44 (0)7592 112 443

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318
Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H315 Causes skin irritation.
H318 Causes serious eye damage.

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

Precautionary statements	P264 Wash contaminated skin thoroughly after handling.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310 Immediately call a POISON CENTER/ doctor.
	P332+P313 If skin irritation occurs: Get medical advice/ attention.
	P362+P364 Take off contaminated clothing and wash it before reuse.

Contains	N'-[3-(Dimethylamino)propyl]-N,N-dimethylpropane-1,3-diamine, 2-[2-(Dimethylamino)ethoxy]ethanol
-----------------	--

Supplementary precautionary statements	P302+P352 IF ON SKIN: Wash with plenty of water.
	P321 Specific treatment (see medical advice on this label).

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Tris(2-chloro-1-methylethyl) phosphate 10-30% CAS number: 1244733-77-4 EC number: 807-935-0 REACH registration number: 01-2119486772-26-XXXX
Classification Acute Tox. 4 - H302
2-(2-Hydroxyethoxy)ethyl 2-hydroxypropyl 3,4,5,6-tetrabromophthalate 5-10% CAS number: 20566-35-2 EC number: 243-885-0 REACH registration number: 01-2119480176-36-XXXX
Classification Aquatic Chronic 3 - H412
N'-[3-(Dimethylamino)propyl]-N,N-dimethylpropane-1,3-diamine 5-10% CAS number: 6711-48-4 EC number: 229-761-9 REACH registration number: 01-2119964469-20-XXXX
Classification Acute Tox. 4 - H302 Acute Tox. 3 - H311 Skin Corr. 1B - H314 Eye Dam. 1 - H318

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

2-[2-(Dimethylamino)ethoxy]ethanol 1-5%		
CAS number: 1704-62-7	EC number: 216-940-1	REACH registration number: 01-2119976346-26-XXXX
Classification Acute Tox. 4 - H312 Skin Corr. 1C - H314 Eye Dam. 1 - H318		
2,2'-Oxydiethanol <1%		
CAS number: 111-46-6	EC number: 203-872-2	REACH registration number: 01-2119457857-21-XXXX
Classification Acute Tox. 4 - H302		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Rinse with water.
Eye contact	Rinse immediately with plenty of water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Temporary irritation.
Ingestion	May cause irritation.
Skin contact	Redness. Irritating to skin.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances:
Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2,2'-Oxydiethanol

Long-term exposure limit (8-hour TWA): WEL 23 ppm 101 mg/m³

WEL = Workplace Exposure Limit.

Tris(2-chloro-1-methylethyl) phosphate (CAS: 1244733-77-4)

DNEL

Workers - Inhalation; Long term systemic effects: 5.82 mg/m³
 Workers - Inhalation; Short term systemic effects: 5.82 mg/m³
 Workers - Dermal; Long term systemic effects: 2.08 mg/kg bw/day
 Workers - Dermal; Short term systemic effects: 2.08 mg/kg bw/day
 General population - Inhalation; Long term systemic effects: 1.46 mg/m³
 General population - Inhalation; Short term systemic effects: 1.46 mg/m³
 General population - Dermal; Long term systemic effects: 1.04 mg/kg bw/day
 General population - Dermal; Short term systemic effects: 1.04 mg/kg bw/day
 General population - Oral; Long term systemic effects: 520 µg/kg bw/day
 General population - Oral; Short term systemic effects: 520 µg/kg bw/day

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

PNEC	Fresh water; 420 - 640 µg/l Intermittent release; 510 µg/l marine water; 64 - 420 µg/l STP; 7.84 mg/l Sediment (Freshwater); 2.92 - 2.96 mg/kg dwt Sediment (Marinewater); 290 - 2960 µg/kg dwt Soil; 1.33 - 1.7 mg/kg dwt
-------------	--

N'-[3-(Dimethylamino)propyl]-N,N-dimethylpropane-1,3-diamine (CAS: 6711-48-4)

DNEL	Workers - Inhalation; systemic effects: 1.47 mg/m ³ Consumer - Inhalation; systemic effects: 0.36 mg/m ³ Consumer - Dermal; systemic effects: 0.08 mg/kg bw/day Workers - Dermal; systemic effects: 0.17 mg/kg bw/day Consumer - Oral; systemic effects: 0.08 mg/kg bw/day
-------------	--

PNEC	Fresh water; 0.0079 mg/l marine water; 0.00079 mg/l Intermittent release; 0.079 mg/l STP; 10 mg/l Soil; 0.0282 mg/kg Sediment (Freshwater); 0.164 mg/kg Sediment (Marinewater); 0.0164 mg/kg
-------------	--

2-[2-(Dimethylamino)ethoxy]ethanol (CAS: 1704-62-7)

DNEL	Workers - Inhalation; Long term systemic effects: 480 µg/m ³ Workers - Inhalation; Long term local effects: 1.07 mg/m ³ Workers - Dermal; Long term systemic effects: 2.33 mg/kg bw/day General population - Inhalation; Long term systemic effects: 85 µg/m ³ General population - Inhalation; Long term local effects: 127 µg/m ³ General population - Dermal; Long term systemic effects: 280 µg/kg bw/day
-------------	--

PNEC	Fresh water; 100 µg/l Intermittent release; 1 mg/l marine water; 10 µg/l STP; 100 mg/l Sediment (Freshwater); 86.957 - 750 µg/kg dwt Sediment (Marinewater); 8.696 - 75 µg/kg dwt Soil; 28.174 - 91.1 µg/kg dwt
-------------	---

2,2'-Oxydiethanol (CAS: 111-46-6)

DNEL	Workers - Inhalation; Long term local effects: 60 mg/m ³ Workers - Dermal; Long term systemic effects: 43 mg/kg bw/day General population - Inhalation; Long term systemic effects: 12 mg/m ³ General population - Inhalation; Long term local effects: 12 mg/m ³ General population - Dermal; Long term systemic effects: 21 mg/kg bw/day
-------------	---

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

PNEC

Fresh water; 10 mg/l
 Intermittent release; 10 mg/l
 marine water; 1 mg/l
 STP; 199.5 mg/l
 Sediment (Freshwater); 20.9 mg/kg dwt
 Sediment (Marinewater); 2.09 mg/kg dwt
 Soil; 1.53 mg/kg dwt

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

Colour	Yellow.
Odour	Characteristic.
Odour threshold	No information available.
pH	pH (concentrated solution): 11
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	1.12 @ 20°C
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	700 mPa s @ 25°C
Explosive properties	No information available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not known.
Comments	Information given is applicable to the product as supplied.
<u>9.2. Other information</u>	
Other information	None.

SECTION 10: Stability and reactivity

10.1. Reactivity

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

Reactivity	See the other subsections of this section for further details.
<u>10.2. Chemical stability</u>	
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<u>10.3. Possibility of hazardous reactions</u>	
Possibility of hazardous reactions	No potentially hazardous reactions known.
<u>10.4. Conditions to avoid</u>	
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
<u>10.5. Incompatible materials</u>	
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<u>10.6. Hazardous decomposition products</u>	
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Summary Based on available data the classification criteria are not met.

ATE oral (mg/kg) 3,182.74

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 4,112.71

Acute toxicity - inhalation

Summary Based on available data the classification criteria are not met.

Skin corrosion/irritation

Summary Causes skin irritation.

Serious eye damage/irritation

Summary Causes serious eye damage.

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

Summary	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Summary	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
<u>Reproductive toxicity</u>	
Summary	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
Summary	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
Summary	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Summary	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Temporary irritation.
Ingestion	May cause irritation.
Skin contact	Redness. Irritating to skin.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Summary Based on available data the classification criteria are not met.

Chronic aquatic toxicity

Summary Based on available data the classification criteria are not met.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	Not applicable.
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	Not applicable.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

HUNTSMAN

BUILDING SOLUTIONS

H2FOAM LITE PLUS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>CAS: Chemical Abstracts Service.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Classification abbreviations and acronyms	<p>Eye Dam. = Serious eye damage</p> <p>Skin Irrit. = Skin irritation</p>
Classification procedures according to Regulation (EC) 1272/2008	<p>Eye Dam. 1 - H318: Skin Irrit. 2 - H315: : Calculation method.</p>
Training advice	<p>Only trained personnel should use this material.</p>
Revision date	<p>03/08/2021</p>
Revision	<p>1</p>
SDS number	<p>1061</p>
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H311 Toxic in contact with skin.</p> <p>H312 Harmful in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H318 Causes serious eye damage.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.