

HUNTSMAN

BUILDING SOLUTIONS



**SPRAY UP TO
4 INCHES THICK
IN ONE PASS**



*Developed with
>20% of Renewable
and Recycled Content*

HEATLOK[®] XT HIGH LIFT

CLOSED-CELL SPRAY FOAM



HEATLOK[®] XT HIGH LIFT

CLOSED-CELL SPRAY FOAM



PRODUCT FEATURES

- >20% recycled & renewable content
- Up to 10 LEED points*
- 0-5 flame spread based on ASTM E-84
- Interior and exterior applications
- Low exo-therm reaction

R-value	Summer 6.7 @ 1 inch* Winter 6.9 @ 1 inch*
ASTM E-84	Summer Flame Spread = 0-5 Winter Flame Spread = 5
Temp Range	Summer 15 - 100°F (-9 - 38°C) Winter 15 - 100°F (-9 - 38°C)
Density	2.17 lb/ft ³
Yield	4500-5000 bd. ft. / set
Max Lift	4"

*Depending on job distance from manufacturer.

**Aged R-value at 4 inches per ASTM C518

REDUCE GLOBAL WARMING IMPACT WITH ULTRA-LOW GWP BLOWING AGENT

Save time and money on the jobsite with Huntsman Building Solutions' Heatlok[®] XT High Lift sprayed up to 4" thick, achieving a required R-value in fewer passes.

Heatlok XT High Lift is our high-performing, versatile, closed cell spray foam insulation for commercial and residential construction. It creates a specially engineered building envelope that provides better thermal resistance, an excellent air barrier and a recognized vapor retarder.

*Complies with the International Building Code[®] (IBC),
the International Residential Code[®] (IRC), and the
International Energy Conservation Code[®] (IECC).*