

HUNTSMAN

BUILDING SOLUTIONS

Experience the benefits of Huntsman Building Solutions OC No-Mix™

- Optimized formulation delivers results at temperatures ranging from 20°F - 120°F
- No-mix formula
- Ideal for meeting Energy Code requirements



OC NO-MIX™

OPEN-CELL SPRAY FOAM



OC NO-MIX™

OPEN-CELL SPRAY FOAM



PRODUCT FEATURES

- Core Density: 0.5 lb/ft³
- R-Value: R-3.9 at 1", R-3.7/inch at greater thicknesses
- Air Barrier at 3.5"
- Can be sprayed in a wide temperature range, making it suitable for applications in any climate
- Low VOC allowing for re-entry after 1 hour, and re-occupancy after 4 hours (at 20ACH)
- Energy savings and durability, while significantly reducing unmanaged moisture and air infiltration.

THICKNESS (inches)	R-VALUE (°F•ft ² •h/Btu)
1	R-3.9
3.5	R-13
4	R-15
5.5	R-20
7	R-26
10	R-36
11.5	R-42

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your energy savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your energy use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on energy. To get the marked R-value, it is essential that this insulation be installed properly.

