

HUNTSMAN

BUILDING SOLUTIONS



Developed with
>15% Renewable
and Recycled Content

HEATLOK[®] HFO EZ

CLOSED-CELL SPRAY FOAM



HEATLOK[®] HFO EZ

CLOSED-CELL SPRAY FOAM



REDUCE GLOBAL WARMING IMPACT WITH HFO TECHNOLOGY, WHICH HAS A GWP OF 1

Heatlok[®] HFO EZ, with an R-value of 7.0 at 1 inch, is designed as a continuous insulation solution with an ultra-low global warming potential blowing agent. Tested and certified as an air barrier, vapor retarder, water barrier and thermal insulation.

Heatlok HFO EZ leverages Honeywell's Solstice[®] Liquid Blowing Agent technology, which has a GWP of 1, 99.9% lower than traditional blowing agents.

PRODUCT FEATURES

- >15% recycled & renewable content
- Superior adhesion and cohesion
- <25 flame spread based on ASTM E-84
- Interior and exterior applications

R-value @ 1 inch	7.0
ASTM E-84	Flame Spread <25 Flame Spread <450
Temp Range	>50°F (10°C)
Max Lift	(2" + 2")
Certification	ER871



Complies with the International Building Code[®] (IBC), the International Residential Code[®] (IRC), and the International Energy Conservation Code[®] (IECC).