



This form must be filled out and posted to comply with building code requirements. Meets IRC Chapter 11 Energy Efficiency Requirements and IECC Chapter 4, Commercial Energy Efficiency Requirements.

The following spray polyurethane foam product(s) has/have been installed.

- | | | |
|--|-----------------------------|-------------------|
| <input type="checkbox"/> Icynene HFO 200 | 2.0-2.4 lbs/ft ³ | IAPMO UES ER-0926 |
| <input type="checkbox"/> Icynene HFO MAX | 2.0-2.4 lbs/ft ³ | ICC-ES ESR-5496 |
| <input type="checkbox"/> Heatlok HFO PRO | 2.0-2.4 lbs/ft ³ | IAPMO UES ER-0565 |
| <input type="checkbox"/> Heatlok HFO High Lift | 2.0-2.4 lbs/ft ³ | ICC-ES ESR-4073 |
| <input type="checkbox"/> Heatlok HFO EZ | 2.0 lbs/ft ³ | IAPMO UES ER-0871 |

Consult International Building Code, Chapter 26-Plastic and International Residential Code (IRC) R316 Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer’s processing guidelines to provide a thermal resistance of:

Area Insulated	Aged R-Value	Thickness**
Vented Attic Floor Area	R- At	inches
Unvented Attic/Under Roof Deck Insulation	R- At	inches
Sloped Ceilings / Cathedral Ceilings	R- At	inches
Walls (Location:)	R- At	inches
Walls (Location:)	R- At	inches
Floors (over an unheated crawl space)	R- At	inches
Crawl Space Perimeter	R- At	inches
Basement Walls	R- At	inches
Other (Location:)	R- At	inches

**Nominal thicknesses are representative of field, spray-applied foam material.

Jobsite Address: _____ **Date of Installation:** _____
Building Contractor: _____
HBS Contractor: _____ **Phone:** _____
Installed By: _____

-Post Near Electrical Panel-