

This form must be filled out and posted to comply with building code requirements. Meets IRC Chapter 11 Energy Efficiency Requirements and IECC Chapter 4, Commercial Energy Efficiency Requirements.

Sealection 500	0.45 lbs/ft ³	ICC-ES ESR-1172 (CCRR-1063)
☐ Sealection NM	0.55 lbs/ft ³	ICC-ES ESR-2668
Foam-Lok 450	0.45 lbs/ft ³	ICC-ES ESR-4242 (CCRR-1091)
Foam-Lok 500	0.45 lbs/ft ³	ICC-ES ESR-4242
Foam-Lok 750	0.70 lbs/ft ³	ICC-ES ESR-4322
OC No-Mix	0.50 lbs/ft ³	CCRR-1123
☐ Classic Ultra Select	0.50 lbs/ft ³	ICC-ES ESR-1826
☐ Classic Plus	0.70 lbs/ft ³	ICC-ES ESR-1826
☐ Classic Ultra	0.50 lbs/ft ³	ICC-ES ESR-1826
☐ APX 1.2	0.45 lbs/ft ³	ICC-ES ESR-3470
☐ Agribalance	0.70 lbs/ft ³	ICC-ES ESR-2600

The following spray polyurethane foam product(s) has/have been installed.

Consult International Building Code, Chapter 26-Plastic and International Residential Code (IRC) R316 Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer's processing guidelines to provide a thermal resistance of:

Area Insulated		Aged R-Value		Thickness**
Vented Attic Floor Area		R-	At	inches
Unvented Attic/Under Roof Deck Insulation		R-	At	inches
Sloped Ceilings / Cathedral Ceilings		R-	At	inches
Walls (Location:)	R-	At	inches
Walls (Location:)	R-	At	inches
Floors (over an unheated crawl space)		R-	At	inches
Crawl Space Perimeter		R-	At	inches
Basement Walls		R-	At	inches
Other (Location:)	R-	At	inches

 $^{^{\}star\star}\mbox{Nominal thicknesses}$ are representative of field, spray-applied foam material.

Jobsite Address:	Date of Installation:			
Building Contractor:				
HBS Contractor:	Phone:			
Installed By:				

-Post Near Electrical Panel-

