

# HUNTSMAN

BUILDING SOLUTIONS

**SPRAY UP TO AN  
R-49 IN A SINGLE  
PASS**



*Developed with  
>20% Renewable  
and Recycled Content*

## HEATLOK<sup>®</sup> HFO HIGH LIFT

CLOSED-CELL SPRAY FOAM



# HEATLOK<sup>®</sup> HFO HIGH LIFT

CLOSED-CELL SPRAY FOAM



## PRODUCT FEATURES

- R-value = 7.4/inch\*
- Spray 6.5" (R-49) in one pass
- Low VOC emission meets requirements for schools and healthcare facilities
- Superior yield, sprayability, adhesion and reduced gun clogging
- Formulated with Solstice<sup>®</sup> Liquid Blowing Agent's Ultra-low GWP of 1

### REDUCE GLOBAL WARMING IMPACT WITH ULTRA-LOW GWP BLOWING AGENT

Heatlok<sup>®</sup> HFO High Lift, Huntsman Building Solutions' first product to leverage an ultra-low Global Warming Potential blowing agent, combines an R-value of 7.4/inch\* with a 6.5" lift to achieve an R-49 in a single pass. Spray to IRC Ceiling insulation code in less time than ever before.

Heatlok HFO High Lift leverages Honeywell's Solstice<sup>®</sup> Liquid Blowing Agent technology, which has a GWP of 1, 99.9% lower than traditional blowing agents. In compliance with the Montreal Protocol designed to lower the use of global warming potential gasses, Heatlok HFO High Lift combines all of the benefits of Heatlok with the industry's fourth generation blowing agent.

R-value	7.4/inch *
ASTM E-84	Flame Spread Index = 1
Application Temp Range	15 - 100°F (-9 - 38°C)
Yield	4500-5000 bd. ft. / set
Max Lift	6.5"



Complies with the International Building Code<sup>®</sup> (IBC), the International Residential Code<sup>®</sup> (IRC), and the International Energy Conservation Code<sup>®</sup> (IECC).

\*Aged R-value per ASTM C518 of R26 @ 3.5 inches.