HUNTSMAN
BUILDING SOLUTIONS

Insulation Certificate

Open-Cell Spray Polyurethane Foam

This form must be filled out and posted to comply with building code requirements. Meets IRC Chapter 11 Energy Efficiency Requirements and IECC Chapter 4, Commercial Energy Efficiency Requirements.

The following spray polyurethane foam product(s) has/have been installed.

☐ Sealection 500	0.45 lbs/ft³	ICC-ES ESR-1172 (CCRR-1063)
☐ Sealection NM	0.55 lbs/ft³	ICC-ES ESR-2668
☐ Foam-Lok 450	0.45 lbs/ft³	ICC-ES ESR-4242 (CCRR-1091)
☐ Foam-Lok 500	0.45 lbs/ft³	ICC-ES ESR-4242
☐ Foam-Lok 750	0.70 lbs/ft³	ICC-ES ESR-4322
☐ OC No-Mix	0.50 lbs/ft³	CCRR-1123
☐ Classic Ultra Select	0.50 lbs/ft³	ICC-ES ESR-1826
☐ Classic Plus	0.70 lbs/ft³	ICC-ES ESR-1826
☐ Classic Ultra	0.50 lbs/ft³	ICC-ES ESR-1826
☐ APX 1.2	0.45 lbs/ft³	ICC-ES ESR-3470
☐ Agribalance	0.70 lbs/ft³	ICC-ES ESR-2600

Consult International Building Code, Chapter 26-Plastic and International Residential Code (IRC) R316 Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer's processing guidelines to provide a thermal resistance of:

Area Insulated	Aged R-Value		Thickness**
Vented Attic Floor Area	R-	At	inches
Unvented Attic/Under Roof Deck Insulation	R-	At	inches
Sloped Ceilings / Cathedral Ceilings	R-	At	inches
Walls (Location:)	R-	At	inches
Walls (Location:)	R-	At	inches
Floors (over an unheated crawl space)	R-	At	inches
Crawl Space Perimeter	R-	At	inches
Basement Walls	R-	At	inches
Other (Location:)	R-	At	inches

**Nominal thicknesses are representative of field, spray-applied foam material.

Jobsite Address: _____ **Date of Installation:** _____

Building Contractor: _____

HBS Contractor: _____ **Phone:** _____

Installed By: _____

-Post Near Electrical Panel-

3315 E. Division Street, Arlington, TX 76011
Tel: 817.640.4900 | 888.224.1533
www.huntsmanbuildingsolutions.com

HUNTSMAN
BUILDING SOLUTIONS