

This form must be filled out and posted to comply with building code requirements. Meets IRC Chapter 11 Energy

Effic	ciency Requirements	and IECC Ch	apter 4, Commercial Er	nergy Efficie	ncy Requirements	S.	
The	following spray poly	urethane foar	n product(s) has/have b	een installed	d.		
	Sealection 500	0.45 lbs/ft <sup>3</sup>	ICC-ES ESR-1172 (CC	RR-1063)	l Cynene OC No-M	0.50 lbs/ft <sup>3</sup>	
	Sealection NM	0.55 lbs/ft <sup>3</sup>	ICC-ES ESR-2668			· ·	
	Foam-Lok 450	0.45 lbs/ft <sup>3</sup>	ICC-ES ESR-4242 (CC	RR-1091)	lcynene Classic 45	0.45 lbs/ft³ 5 ICC-ES ESR-5498	
	Foam-Lok 500	0.45 lbs/ft <sup>3</sup>	ICC-ES ESR-4242		Icynene	0.50 lbs/ft <sup>3</sup> ICC-ES ESR-5497 (CCRR-0560	
	Foam-Lok 750	0.70 lbs/ft <sup>3</sup>	ICC-ES ESR-4322		☐ Ultra 50		
	OC No-Mix	0.50 lbs/ft <sup>3</sup>	CCRR-1123			0.55 lbs/ft <sup>3</sup>	
	Classic Ultra Select	0.50 lbs/ft <sup>3</sup>	ICC-ES ESR-1826		Xpress 55		
	Classic Plus	0.70 lbs/ft <sup>3</sup>	ICC-ES ESR-1826			0.70 lbs/ft³ 5 ICC-ES ESR-5495	
	Classic Ultra Agribalance	0.50 lbs/ft <sup>3</sup> 0.70 lbs/ft <sup>3</sup>	ICC-ES ESR-1826 ICC-ES ESR-2600		lcynene High-R 80	0.6 - 0.8 lbs/ft <sup>3</sup>	
	Area Insulated  Vented Attic Floor			R-Value	Thickness**		
	Vented Attic Floor		R-	At	inches		
	Unvented Attic/Under Roof Deck Insulation				At	inches	
	Sloped Ceilings / (	ngs	R-	At	inches		
	Walls (Location:		)	R-	At	inches	
	Walls (Location:		)	R-	At	inches	
	Floors (over an unheated crawl space) Crawl Space Perimeter				At	inches	
					At	inches	
	Basement Walls			R-	At	inches	
	Other (Location:		)	R-	At	inches	
	**Nominal thicknesses are	representative of fi	eld, spray-applied foam materia	d.			
Jol	osite Address:				Date of Installation:		
Bui	Iding Contractor:						
HBS Contractor:					Phone:		
Ins	talled By:						

-Post Near Electrical Panel-

