

HUNTSMAN

BUILDING SOLUTIONS

Superior Yield
and Industry
Leading R-value



19% Renewable
& Recycled
Product

HEATLOK[®] HFO[™] PRO

CLOSED-CELL SPRAY FOAM



HEATLOK[®] HFO[™] PRO

CLOSED-CELL SPRAY FOAM



PRODUCT FEATURES

- R-value = 7.4 @ 1 inch R-11 @ 1.5 inches
- 20% yield increase and improved flame spread over Heatlok Soy 200 Plus
- 5% more recycled & renewable content than Heatlok Soy 200 Plus
- Superior adhesion and compressive strength
- Passes NFPA 285 with brick, stone and masonry exterior.
- Class II vapor retarder at 1 inch
- Exceeds ASHRAE 90.1 insulation requirements at 1.5 inches
- ABAA Certified

COMBINES THE STRENGTHS OF HEATLOK WITH THE 4TH GENERATION BLOWING AGENT.

Heatlok[®] HFO[™] Pro, with an R-value of 7.4 at 1 inch, is designed as a continuous insulation solution with an ultra-low global warming potential blowing agent. Tested and certified as an air barrier, vapor retarder, water barrier and thermal insulation.

Heatlok HFO Pro leverages Honeywell's Solstice[®] Liquid Blowing Agent technology, which has a GWP of 1, 99.9% lower than traditional blowing agents, and is in compliance with the Montreal Protocol designed to lower the use of global warming potential gases.

| | |
|---------------------------|--|
| R-value | 7.4 @ 1 inch |
| ASTM E-84 | Flame Spread Index = 12 Smoke Developed = 350-400 |
| Application Temp Range | 15 - 100°F (-9 - 38°C) |
| Yield | 5,000 bd. ft. / set |
| Max Single Pass Thickness | 2" + 2" |
| Certification | Evaluation Report 565 |



EXTERIOR WALL SYSTEM COMPONENT
IN ACCORDANCE WITH NFPA 285
SEE BUILDING MATERIALS DIRECTORY
ALSO CLASSIFIED IN ACCORDANCE WITH ASTM D1192
FILE R30809